



Let's grow together®

## Select Hopper Bin Sizes (Additional Models Also Available) Including 40° Roof, SPRING-LOCK® Lid and HYDROSHIELD® Weather Guard

MODEL NUMBER‡	DIAMETER IN FEET (METERS)	# OF RINGS	HOPPER ANGLE	AUGER FILL – U.S.			AUGER FILL – METRIC			PNEUMATIC FILL – METRIC		
				CAPACITY		HEIGHT TO FILL	CAPACITY		HEIGHT TO FILL	CAPACITY		HEIGHT TO FILL
				40 LB./CUBIC FT.			641 KG/M <sup>3</sup>			641 KG/M <sup>3</sup>		
				TONS	CUBIC FEET	FT-IN	METRIC TONS	CUBIC METERS	M	METRIC TONS	CUBIC METERS	M
45-00601	6 (1.8)	1	60°	3.1	156.9	11' 6"	2.8	4.4	3.5	2.7	4.2	3.35
45-00602	6 (1.8)	2	60°	4.6	231.9	14' 2"	4.2	6.6	4.3	4.0	6.4	4.17
45-00723	7 (2.1)	3	67°	9.0	448.4	20' 1"	8.1	12.7	6.1	7.9	12.3	5.92
45-00724	7 (2.1)	4	67°	11.0	549.8	22' 9"	10.0	15.6	6.9	9.7	15.2	6.73
45-00902	9 (2.7)	2	60°	12.0	597.6	18' 3"	10.8	16.9	5.7	10.4	16.0	5.28
45-00903	9 (2.7)	3	60°	15.4	767.6	20' 11"	13.9	21.7	6.4	13.3	20.8	6.10
45-00904	9 (2.7)	4	60°	18.8	937.6	23' 7"	17.0	26.6	7.2	16.4	25.8	6.91
45-00905*	9 (2.7)	5	60°	22.2	1,107.6	26' 3"	20.1	31.4	8.0	19.4	30.3	7.72
45-01203	12 (3.7)	3	60°	29.7	1,484.4	24' 9"	26.9	42.0	7.5	25.7	40.1	7.14

‡Add "PN" after part number for pneumatic fill model.

\*Includes ladder safety cage. Safety cages are included as a standard feature for bin ladders exceeding 20 feet (6 meters) in height, conforming with U.S. OSHA standards.