



## ENDURA® Direct-Drive Fan Specifications Composite Shroud & Shutter Doors / HDPE Cone

STANDARD MOUNT		U.S. MEASURE				METRIC				Air Flow Ratio	Bess Lab Test No.	230V Power
Part No.	Hz	Static Pressure .10"		Static Pressure .15"		Static Pressure 25 Pa		Static Pressure 37.5 Pa				
		CFM	CFM/Watt	CFM	CFM/Watt	CMH	CMH/Watt	CMH	CMH/Watt			
56555-1	41.8	32,000	19.7	30,500	17.6	54,300	33.6	51,900	30.0	0.86	20084	60 Hz 1 Ph
	38.1	28,900	22.5	27,100	19.7	49,000	38.3	46,100	33.5			
	33.0	24,400	27.5	22,100	23.0	41,400	46.8	37,600	39.1			
	28.1	18,200	29.8	14,800	22.5	31,000	50.6	25,200	38.3			
	23.2	11,900	31.8	6,600	15.9	20,300	54.0	11,300	27.0			
56555-2	42.0	32,100	20.0	30,400	17.7	54,500	34.0	51,600	30.1	0.86	20085	60 Hz 3 Ph
	38.2	28,800	22.8	27,100	19.9	48,900	38.8	46,100	33.7			
	33.2	24,400	27.6	21,900	22.7	41,400	46.9	37,200	38.6			
	28.2	18,300	29.9	14,700	22.4	31,100	50.8	25,000	38.1			
	23.2	11,400	30.5	6,500	15.5	19,400	51.8	11,000	26.4			
56555-2	42.0	31,800	19.8	30,500	17.9	54,100	33.7	51,700	30.4	0.86	20086	50 Hz 3 Ph
	38.2	28,700	22.6	27,000	19.9	48,900	38.4	45,900	33.9			
	33.2	24,200	27.1	21,900	22.6	41,100	46.0	37,200	38.5			
	28.2	18,300	30.0	14,600	22.3	31,000	51.0	24,800	37.9			
	23.2	11,500	31.0	6,400	15.7	19,600	52.7	10,900	26.6			

