



## *CAGE WATERING QUICK REFERENCE SHEET*

### POST INSTALLATION CHECKLIST

- Flush all lines at maximum pressure
- Be sure filters are installed correctly
- Check that Float Balls are installed in Brooding Sections
- Make sure that the cups sit upright
- Check for any leaking or dripping pipe connections
- Maintain house temperatures above freezing or drain lines and cups completely

### INITIAL START-UP PROCEDURE

- Clean all dirt out of cups
- Flush all air out of lines
- Check for any leaking or dripping pipe connections

### OPERATING DURING BIRD GROW-OUT (BROOD-GROW SYSTEMS)

- WEEK 1** Start birds with Float Balls on all cups. Set pressure at 4-6 p.s.i. (27-41 kPa). Adjust as necessary. Generally, a higher pressure provides less water. Do not attempt to run below 2 p.s.i. (13 kPa). Cups should be adjusted completely down for easy access by the birds.
- WEEK 2** Remove Float Balls at 7 to 10 days of age. Reduce pressure to 3-4 p.s.i. (20-34 kPa) for several days to allow easy triggering of the valves. Begin to raise the cups. Keep the lip of the cup even with the bird's neck.
- WEEK 3** to full age Maintain proper water cup height throughout the grow-out. After 4 weeks, maintain water pressure at 6-8 p.s.i. (41-55 kPa).

### OPERATION ADULT BIRDS (LAYER SYSTEMS)

- Maintain water pressure at 6-8 p.s.i. (41-55 kPa).

### MAINTENANCE BETWEEN BATCHES

- Flush all air out of the lines
- Flush each line at full pressure for 20 minutes to remove deposits and sediments
- Check pressure drop across water filter - clean or replace if necessary
- Check pressure gauges, regulator, and shut off valves for proper operation
- Maintain house temperatures above freezing or drain lines and cups completely

**MW751C2-589**

---

**CHORE-TIME EQUIPMENT, A DIVISION OF CTB, INC.**  
**P.O. BOX 2000**  
**MILFORD, INDIANA 46542-2000 U.S.A.**

## WATER QUALITY

Water quality is very important for proper operation of the system. Consider the following:

**HARDNESS**-(Calcium and Magnesium) above 14GPG (grains per gallon) a water softener should be used.

**PH**-under 6.5 a neutralizing filter is recommended.

**IRON**-above 0.5 ppm (parts per million) should be treated with a water softener, a mechanical filtration system, or chlorinating depending on raw water hardness.

## PRECAUTIONS

Do not over-chlorinate. The maximum concentration is 5 ppm (parts per million) for extended periods and 10 ppm for flushing only.

Do not chlorinate 2 days before or after medication is used.

**To Chlorinate:** Mix a stock solution of 3/4 ounce of household bleach (5-1/4% Sodium Hypochlorite) per gallon or 5.9 ml of bleach per liter of water. Set the proportioner to dispense at a rate of one ounce per gallon or 7.8 ml per liter.

Some vitamins and medications are syrup type liquids or are sugar based. Avoid these types of compounds. These compounds may leave a slimy deposit on the valve seals preventing them from sealing properly.

Some pumps and/or special purpose gas injectors may add excessive air to the water supply. For proper operation of the system in these cases an Air Remover Kit is recommended to remove excess air from the system. Contact your local CHORE-TIME/SWISH distributor.

## TROUBLESHOOTING GUIDELINES

All cups running over:

- Check for pressure drop from water supply
- Water Filter clogged
- Check for proper pressure regulator setting
- Check that control valves are fully opened
- Supply hoses pinched

Sections of cups running over:

- Check for air in the line

Individual cups running over:

- Usually trash in the valve. Trigger valve to flush particles out of valve. Replace valve if necessary.

Birds not getting enough water:

- Restricted flow (see above)
- Pressure set too high on young birds
- Waterer cups adjusted too high

---

Contact your nearby CHORE-TIME/SWISH distributor or representative for additional information or parts

Please have the following information available when you call: 1. Year the system was purchased,

2. Line length and cup spacing, and

3. Trigger length and colors of components